



**Specifications Philips LED Panel**  
**Coreline RC132V 24.5-34.5W**  
**3100-4300lm - 840 Cool White |**  
**60x60cm - UGR <19**

[View Product](#)

## General Information

|                          |                                       |
|--------------------------|---------------------------------------|
| SKU                      | 246032                                |
| EAN                      | 8719514950313                         |
| Brand                    | Philips                               |
| Manufacturer Name        | RC132V G5 31_36_43S/840 PSU W60L60 OC |
| Any Lamp all-in warranty | 5 Years                               |
| Average Lifetime (h)     | 50000                                 |
| Series                   | RC132V                                |

## Technical Information

|                             |                 |
|-----------------------------|-----------------|
| Technology                  | LED Integrated  |
| Replaces (Watt)             | 4x18            |
| Wattage                     | 34.5            |
| Voltage (V)                 | 220-240         |
| Dimmable                    | Not Dimmable    |
| Colour Code                 | 840 Cool White  |
| Colour temperature (Kelvin) | 4000 Cool White |
| Colour Rendering (Ra)       | 80-89           |
| Colour of Light             | White           |
| Light colour options        | Single Color    |
| Light Distribution          | Symmetrical     |

|                          |                   |
|--------------------------|-------------------|
| Luminous Flux (Lumen)    | 4300              |
| Luminous Efficacy (lm/W) | 125               |
| IP-rating                | IP44              |
| Impact Protection (IK)   | IK03 - 0.35 joule |
| Fixture Connection       | Terminal, 2-pole  |
| Driver Included          | Yes               |
| Power factor             | >0.90             |
| Product Type Category    | LED Panel         |

## Fixture Information

|                       |                                |
|-----------------------|--------------------------------|
| Mounting Method       | Recessed                       |
| Unified Glare Rating  | < 19 - for offices and schools |
| Optical Cover         | PS (Polystyrene)               |
| Operating Temperature | -10 to +40                     |
| Emergency Lighting    | No Emergency Unit              |
| Colour of the Fixture | White                          |
| Housing               | Steel                          |
| Colour of material    | White                          |

## Dimensions

|                |         |
|----------------|---------|
| LED panel size | 60x60cm |
| Length (mm)    | 595     |
| Width (mm)     | 595     |
| Height (mm)    | 11      |



Order from the **largest lighting specialist** in Europe



**Customised** quotation

## Sensor Information



Up to **7 years warranty**



**Easy** return process

|                |           |
|----------------|-----------|
| Type of sensor | No Sensor |
|----------------|-----------|